



Trailing-edge dimmers tested with the L05021 MINIDIM Driver

- JULY 2009 -

Manufacturer	Dimmer	Minimum LED-Load	Minimum Dim-Range	Stability
BERKER	286710 (same as Insta 51190)	2.5 Watt	20%	OK
BERKER	- (same as Insta 53128 R)	-	25%	NOT STABLE
BUSCH J	6513U-102	7.5 Watt	20%	OK
ELARI	ATD 315	2.5 Watt	20%	OK
ELARI	ATD 600R	7.5 Watt	20%	OK
EPV	PAB 315	2.5 Watt	20%	OK
GIRA	- (same as Insta 51190)	2.5 Watt	20%	OK
GIRA	- (same as Insta 53128 R)	-	25%	NOT STABLE
INSTA	51190	2.5 Watt	20%	OK
INSTA	53128 R	-	25%	NOT STABLE
INSTA	FUNK 576650 22	10 Watt	30%	OK
INSTA	51040	2.5 Watt	20%	OK
JUNG	1254 UDE (same as Insta 53128 R)	-	25%	NOT STABLE
JUNG	225TDE	2.5 Watt	20%	OK
LUTRON	LPRPM-4A	2.5 Watt	15%	OK
LUTRON	GRAFIK INTEGRAL GXI	2.5 Watt	15%	OK
OPUS	852395	2.5 Watt	30%	OK
PEHA	433HAB	2.5 Watt	20%	OK
SCHNEIDER	ATD 315	2.5 Watt	20%	OK
SCHNEIDER	600R	7.5 Watt	20%	OK
SIEMENS	5 TC8 284	7.5 Watt	15%	OK

